

# AquaRite® NEO LS



YEARS OF WARRANTY  
**3** STANDARD **4<sup>TH</sup>** 8000 HOURS  
 Cell



As defined by EN 17645.  
 Go to report pages to see the complete detail by item.

## BUILT FOR TODAY, READY FOR THE FUTURE

- **Salt chlorinator** with control of standard water parameters: pH, redoX and temperature
- **Remote management** of the water quality thanks to Wi-Fi connection or Ethernet connection kits as an option
- **Transparent cell** to provide visual control of chlorine production
- **pH, redoX and temperature kits** available as an option
- **Easy installation** of accessories

### INCLUDED



Chlorine generation




Touch Screen 4.3"



Salt water & Sea water compatible



Modbus protocol



Manage all your parameters using the free custom-designed app **Hayward® Poolwatch**

Description	AQR-NEO-1LS	AQR-NEO-2LS	AQR-NEO-3LS
Maximum production g Cl/h	15 g/h	30 g/h	45 g/h
Average volume of the pool	75 m³	150 m³	200 m³
Salt concentration	From 1.5 g to 100 g of NaCl		
Display	4.3" Touch Screen		
Choice of languages	ES (Spanish) - EN (English) - FR (French) - DE (German) - IT (Italian) - TR (Turkish) - CS (Czech) - PT (Portuguese) - NL (Dutch) - PL (Polish) - HU (Hungarian) - RU (Russian) - HR (Croatian)		
Power supply	230 VAC 50/60 Hz		
Dimensions	254 x 298 x 115 mm		
Box	Black and white ABS flame retardant plastic		
Output	7 V 15.5 A	9.5 V 15 A	12 V 15 A
Consumption	120 W	150 W	190 W
Self-cleaning	By polarity inversion, can be configured by the installer		
Flow detection	●	●	●
Gas detection	●	●	No
Alarms	Low production / No flow / AL3 for injection of pH adjuster / AL4 for cell configurable		
Maximum temperature	45 °C		
Hydrolysis cell	5 titanium plates	7 titanium plates	10 titanium plates
Minimum flow	5 m³/h	9 m³/h	9 m³/h
Dimensions of the plates	200 x 45 mm	200 x 45 mm	400 x 45 mm
Cell holder material	Transparent PVC plastic		
Cell attachment method	Threaded for easy installation of the cell		
Flexible hose connector diameter	63 mm		
Cell dimensions	355 x 305 x 305 mm		520 x 305 x 305 mm
Cell cable	(3 x 4) x 1.5 m (extension cable available, refer to the catalogue of spare parts)		(2 x 4) x 1.5 m
Maximum pressure	4 kg/cm²		
Maximum temperature	45 °C		
pH kit	BPENG-OPTION-PH (premium plastic probe) / BGKBPER (glass probe) - (peristaltic pump 1.5 L/h)		
ORP kit	E-OPTION-REDOX (premium plastic probe) / EG (glass probe)		
Temperature kit	T-OPTION-TEMP		
Wi-Fi module	RS4WI-OPTION-W		
Ethernet module	RS4NET-OPTION-L		
Pool anode	KV02		

AQUARITE® NEO LS

TRANSPARENT CELL

OPTIONS AVAILABLE



Transparent probe holder in PVC included



Flow switch included



Plastic pH kit



ORP probe plastic kit



Temperature kit



Wi-Fi module



Ethernet module