



As defined by EN 17645.
Go to report pages to see the complete detail by item.




Control Station NG

CONTROL YOUR POOL REMOTELY

- **A single control box** for remote device regulation and control
- **4 auxiliary relays** for control and management of filtration cycles, heat regulation, lighting and also for an additional equipment (outdoor lighting, water feature...)
- **Three 230V output voltage auxiliary relays** including dosing pump for pH and disinfectant
- Optional probe for free chlorine measurement
- Two dosing pumps for **pH regulation and liquid chlorine injection***
- **Wifi module:** simple, trouble-free remote management

NEW



CONTROL STATION NG

AVAILABLE OPTIONS

Description	CST-CTL-PHORPNG Complete box - pH & probe	CST-CTL-BCNG Box only
Choice of languages	ES (Spanish) - EN (English) - FR (French) - DE (German) - IT (Italian) - TR (Turkish) - CS (Czech) - PT (Portuguese) - NL (Dutch) - PL (Polish) - HU (Hungarian) - RU (Russian) - HR (Croatian) - HE (Hebrew) - ZH (Chinese)	
Display	4.3" Touch screen	
Power supply	230 Vac 50 Hz	
Dimensions	270 x 220 x 115 mm	
Electronic box	Black Polycarbonate fireproof plastic	
Protection Lid	Blue ABS fireproof plastic	
Main control outputs	Filtration (Smart mode activated + VSTD Pump control) / Lighting (12 Vac 50W) / Heating	
Additional control outputs	4 additional auxiliary relays, configurable by the user	
Maximum temperature	45 °C	
Flow detection	Mechanical flow switch	
Alarms	No flow / AL3 for liquid injection / TANK (if tank level installed)	
Temperature kit	Included	
pH control	Yes (Goldline probe)	No
ORP control	Yes (Goldline probe)	No
Wifi module	Included	No
Goldline pH probe kit	AQR-CTL-KITPH	
Standard pH probe kit	BPENG-OPTION-PH	
ORP Goldline probe kit	AQR-CTL-KITORP	
Standard ORP probe kit	AQR-CTL-KITORP2	
Free chlorine amperometric probe	H-OPTION-CL	
Free chlorine membrane probe	H-OPTION-CL2	
Conductivity probe	I-OPTION-SAL	
WiFi Module	RS4WI-OPTION-W	
Ethernet Module	RS4NET-OPTION-L	
Detachable Touch Screen	CTS-OPTION-TS	
Detachable TFT screen	AQR-PLUS-PANL	
Empty tank detection	AQR-PLUS-CANNE	
Deposit dosing storage	09950050000 (50L) / 09950100000 (100L)	
Pool terre	KV02	



pH kit (standard)



pH kit (Goldline)



ORP kit (Goldline)



Temperature kit



Free amperometric probe



Free chlorine membrane probe



WiFi module



ORP kit (standard)



Ethernet module



Detachable touch screen



Detachable TFT screen



Flow switch included



Deposit dosing storage